

Bush Hog® TOUGH Air Tunnel Side Discharge Finishing Mowers

BUSH HOG® TOUGH FEATURES

TOUGH Fabricated 7 Gauge Decks

TOUGH Commercial Grade Greaseable Spindles

TOUGH Cat 3 Drivelines

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Kevlar Reinforced Belt

TOUGH Powder Coat Paint



Model ATH900

MODELS	ATH600	ATH720	ATH900
Cutting Width	60 inches	72 inches	90 inches
Cutting Height (1/2 inch increments)	1 to 6 inches	1 to 6 inches	1 to 6 inches
Tractor HP Range	15 - 35 PTO	20 - 40 PTO	35 - 55 PTO
Type Hitch	Category I	Category I	Category I
Size Blades	1/4 x 21 1/2 x 21 inches	1/4 x 21 1/2 x 25 inches	1/4 x 3 x 31 1/2 inches
Number of Blades	3	3	3
Blade Tip Speed	18,231 FPM	18,272 FPM	15,621 FPM
Blade Overlap	1 1/2 inches	1 1/2 inches	2 1/4 inches
Blade Uplift	Parallel	Parallel	Parallel
Driveline Size	ASAE Category 3	ASAE Category 3	ASAE Category 3
Front Roller Size (optional)	3 x 5 inches	3 x 5 inches	3 x 5 inches (2)
Discharge	Right Side	Right Side	Right Side
Deck Plate	7 gauge	7 gauge	7 gauge
Tire Size	31/4 x 10 1/4 inches (solid tire)	31/4 x 10 1/4 inches (solid or pneumatic tire)	13 x 5 inches (solid or pneumatic tire)
Belt	"B" Size Kevlar	"B" Size Kevlar	"C" Size Kevlar
Gearbox	45 HP	45 HP	55 HP
Tractor PTO Speed	540 RPM	540 RPM	540 RPM
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler	Spring Loaded Idler
Approximate Weight	570 lbs	610 lbs	1164 lbs
Options	Front Roller Roller Bearing Kit	Front Roller Roller Bearing Kit	Front Roller Roller Bearing Kit
Warranty	1 year limited warranty with a 5 year gearbox limited warranty		

FEATURES

Floating top link • High blade tip speeds • Available in major tractor colors